



Nanjing Tianshi New Material Technologies Co., Ltd

Caofang Road Liuhe Development Zone Nanjing, China

Zip Code: 211500

TEL: 86-025-58393864 58393872

FAX: 86-025-58393532 58393878

OE-6301

PE Wax Emulsion

Chemical Composition

Oxidized polyethylene wax

Technical Parameters

Nature of the product	OE-6301
Appearance	Light yellow emulsion
Melting point °C	130
pH	7-9
Ionic nature	Non
Solid content %	34-36

Characteristics and Purposes

- Oxidized polyethylene wax is a synthetic wax. It has different melting point, hardness, and density, polyethylene wax is a very good choice under the high temperature condition. Wax emulsion refers to the water-based system with the particle size distribution below 1 μ m, distinguished by the emulsion iconicity, it can be non-ionic, anionic, and cationic. Wax emulsion is different from wax dispersion, it has no matting effect, and be used for coating and inks which has high requirement on gloss.
- OE-6301 with high gloss and high transparency, can improve hand-feeling, abrasion& scratch resistance, especially suitable for coatings which need high gloss and transparency.
- Be used for fabric finish, coating, ink, paper, leather, OE-6301 provides abrasion& scratch

resistance, high gloss, and soft hand-feeling.

- OE-6301 can be used for water-based coatings, and polish fields like floor, leather, furniture, automotive, paper and others, as well as the production of liquid shoe polish, metal mold release agents, and other industries.
- To ensure the uniformity of the product, please shake it well before use.
- Please try its suitability beforehand when mixing with other substances, especially considering the pH value.
- This description is for reference and does not have any guarantee.

Contents and Usage

- Added directly into systems, stir and use, dosage is generally between 5-10 %.

Packaging and Storage

- 200 kg/plastic drum or 1000kg/IBC.
- Store in an airtight, cool place, and take care to prevent freezing.
- The shelf life of the original packaging at room temperature is 12 months. Once the container is opened, it is recommended to use it within a short period of time.
- This product is non-dangerous goods. Please store it away from ignition sources and strong oxidants.