

SALES SPECIFICATION

HEXANE

Property	Unit	Standard	Requirement
Appearance		Visual appearance	Transparent, sediment free
Density at 15 °C	g/cm ³	EN ISO 12185	0.6650 - 0.6850
Initial Boiling Point	C fok	EN ISO 3405	min. 64
Final Boiling Point	C fok	EN ISO 3405	max. 69.5
n-Hexane	%(m/m)	ASTM D 5134	min. 55
Metil-cyclo-Pentane	%(m/m)	ASTM D 5134	max. 20
Cyclohexane	%(m/m)	ASTM D 5134	max. 1.8
C6 i-alkanes	%(m/m)	ASTM D 5134	max. 35
n-Heptane	%(m/m)	ASTM D 5134	max. 3
Összes aromás (ppm)	mg/kg	MSZ 1043	max. 10
Benzene	mg/kg	MSZ 1043	max. 10
Colour (HAZEN)		ISO 6271	max. 20
Sulphur Content	mg/kg	EN ISO 20846	max. 2.0
Existent Gum	mg/100cm ³	EN ISO 6246	max. 5
Bromine Number	gBr/100g	ISO 3839	max. 0.010
Water		MSZ 1044 @ 8.1.	Exempt
Doctor Test		ASTM D 4952	Negativ
As	mg/kg	EPA 6020A:2007	less than 1.00
Pb	mg/kg	EPA 6020A:2007	less than 1.00