

Product Description – Polymer Emulsions

KEMILINE[®] TA 332

Acrylic thickener for paint, textile, flocking and coating applications.

Field: Paint, textile, flocking and coatings

- Properties
- Provides foam free mixtures.
 - Extremely soluble and easy to mix with other chemicals.
 - Provides high viscosity to the final paste.

Chemical nature: Acrylic emulsion

Technical Data	Appearance	: Low viscous, white liquid.
	Solid content	: 27 – 29 % (1 g, 30 min at 150 °C)
	pH value	: 2,0 – 4,0 (at 20 °C)
	Viscosity	: 15 – 45 cps (B. Field, 1 / 100 at 20 °C)
	Packaging	:120 kg PE drums /160 kg PE drums 1000 kg IBC containers
	Shelf life	: 12 months at 5 - 35 °C.
	Frost	: Store under frost-free conditions.
	Safety	: No special precautions.

T_g and MFFT values are typical properties of the emulsions and should not be considered as specifications. Certificates of the analysis (COA) are available upon request.

Application: KEMILINE TA 332 is resistant to the shear force which may occur because of high stirring speeds. The recommended quantity is max. 70 g / kg (%7) of the total printing mixture

Information given in this document represents our latest know ledge and provides data on the physical properties and possible uses of Kemiteks products. Kemiteks does not assume any liability on the accuracy and completeness of the data given herein. Kemiteks does not give any warranty, expressed or implied, for the suitability of the products to any particular application. Kemiteks strongly recommends the customers to make their own trials in advance, to test the performance, acceptability and suitability of her delivered products on customer's particular applications under customer's prevailing conditions, before full scale industrial runs.

KY 72/TBD 73 009 Rev.02 11.08.2016 1/2

KEMİTEKS Kimya San. ve Tic. A.S.
Omerli Mah. Gulce Sok. No: 80
34555 Arnavutkoy – ISTANBUL / TURKEY
Tel: +90 212 771 2828 Faks : +90 212 771 2837
info@kemiteks.com
www.kemiteks.com

Product Description – Polymer Emulsions

KEMILINE[®] TA 332

Important issues on storage and use of the product:

- Shelf life of the product is 12 months from the production date, printed on the label and indicated in certificates of analysis, as long as kept between 5-35 °C and away from direct sunlight and freezing conditions.
- Product needs to be kept in hygienic conditions to be away from microbiological attacks, although has certain biocides in the formulation. Addition of extra biocides may be required depending on the conditions of the site such as high storage temperatures, long storage durations and suspects of infection of the product during handling. Bulk storage tanks need to be inspected and cleaned up from time to time depending on the conditions.
- Metal parts suspected to corrode should not be allowed to come into direct contact with this product during storage and use.
- It is recommended to keep storage tanks, IBCs and drums tightly closed, avoiding loss of moisture and keeping the headspace saturated with water vapor to eliminate formation of films at top and keeping the product away from microbiological attacks.
- Packed material in IBCs and drums is recommended to be stirred prior to use.
- Product may tend to give lumps and skins due to its film forming nature. Straining through a coarse filter is recommended prior to use for this reason.
- Product should be handled in compliance with usual safety measures. Material safety data sheets should be examined, prior to use the product. Personal protective equipment such as gloves and goggles are recommended to be used when handling the product.

Please contact our distributors, agents and sales representatives for further information and assistance.

Information given in this document represents our latest knowledge and provides data on the physical properties and possible uses of Kemiteks products. Kemiteks does not assume any liability on the accuracy and completeness of the data given herein. Kemiteks does not give any warranty, expressed or implied, for the suitability of the products to any particular application. Kemiteks strongly recommends the customers to make their own trials in advance, to test the performance, acceptability and suitability of her delivered products on customer's particular applications under customer's prevailing conditions, before full scale industrial runs.

KEMITEKS Kimya San. ve Tic. A.S.
Omerli Mah. Gulce Sok. No: 80
34555 Arnavutkoy – ISTANBUL / TURKEY
Tel: +90 212 771 2828 Faks : +90 212 771 2837
info@kemiteks.com
www.kemiteks.com